

TechnoDrive™ Features

- Proportional hydraulics
- Closed loop press control
- Jomar RPM plastifier motor
- Remote diagnostics capability
- Digital press transducers
- High efficiency 50 HP motor
- Non cushioned cylinders

Standard Features

- Programmable control system with touch screen
- Screw speed tachometer
- Running time recorder
- Alarm system (visual and audible)
- Two pressure blow air
- High and low plastifier temperature alarms
- Cycle time indicator
- Preform hot water manifold
- Blow mold cooling manifold
- Laser Electric preform detector
- Current ANSI/EC safety standards
- Ceramic heater bands
- Integrated heat controls
- Resettable cycle counter
- Retains over 250 sets of process parameters
- Two pressure preform injection
- Internal and external cooling



Jomar®

115 East Parkway Drive
Egg Harbor Township, NJ 08234 USA
Website: <http://www.jomarcorp.com>
Email: info@jomarcorp.com

High Production Machine



Dry cycle time 35% faster than standard Model 65

General Specifications

Average Power Consumption	27.5 kW*	
Dry Cycle Time	1.8 Seconds	
	US	Metric
Preform Clamp	52 US tons	47 metric tons
Casting Area	29.7 ins ²	192 cm ²
Blow Mold Clamp	17.0 US tons	15.4 metric tons
Shut Height	9.00"	228.6 mm
Press Stroke	5.00"	127.0 mm
Maximum Die Set (W x L)	17.00" x 26.00"	432 mm x 660 mm
Max Trigger Bar Length**	25.75"	654 mm
Max Swing Radius	25.39"	645 mm
Oil Tank Capacity	100 gallons	378.5 liters
Plastification Rate	41 grams/sec. with 2" (50.8mm) screw (HDPE)	
Shot Size	205 grams based upon 5 seconds (HDPE)	
Motor Size	Standard 50 hp (37.3 kW)	
Recommended Power Service (Machine Only)	200 amps @ 380V - 460V, 3 phase, 50 - 60 hz	
Total connected load	55.0 kW	

Machine Dimensions

	US	Metric
Length	115"	292 cm
Width	78"	198 cm
Height with 2.0" (50.8 mm) 30:1 Vertical Screw	134"	341 cm
Installed Weight	16,480 lbs	7,475 kg

* Energy consumption reduction contingent upon container specification and material process

** For information on available trigger bar lengths please contact Jomar